



1204 DHS ES ISO Diesel



**Manufactured
in
Germany**

Order No. 122 005
Synchronous alternator

Engine type HATZ 2G 40

Standard outfit

1 x Schuko 230 V/16 A,
2 x CEE 230 V/16 A,
1 x CEE 400 V/16 A,
Overload protection,
Voltmeter,
Isometer,
Operating hour meter,
Set of wheels,
Central crane handling device

Application areas*

Electric tools up to	8700 W	5700 W
Gardening and construction equipment up to	5800 W	3800 W
Inverter welding sets up to	4,5 mm	
Compressors, pumps up to	4400 W	2900 W

400 V 230 V

*As the power needs of each consumer are influenced by various factors, no claims can be derived from this table.

Specifications

Max. output [LTP] kVA/kW	15,8/12,6	10,4/9,4
Prime Power [PRP] kVA/kW	11,0/8,8	6,5/5,8
Nominal voltage	400 V 3~	230 V 1~
Nominal current	15,9 A 3~	28,3 A 1~
Efficiency factor cos (phi)	0,8	0,9
Frequency / Type of protection	50 Hz/IP 23	
Engine version	2 Cylinder 4-stroke	
Engine capacity	654 cm ³	
Power at 3000 rpm	15,4 kW/20,9 HP	
Fuel / Tank capacity (litres)	Diesel/17	
Running-time at 3/4 load approx.	7,5 h	
Start-up system	Electric start incl. battery	
Sound power level LWA	98 dB(A)	
Sound pressure level (7 m)	73 dB(A)	
Weight approx. kg	275	
Dimensions L x W x H in mm	1270 x 830 x 920	

Available accessories	Order No.
Automatic control panel	163 000 (not retrofit)
Remote control	164 000
One axle trailer FG 75 ST	341 100
One axle trailer FG 75 HV	341 101